




OUTDOOR



# VERVE ADJUSTABLE SPOT 60



## Specifications

Mounting	Surface/Spike/Tree/Wall/Pole Mounted
Wattage	6W
Voltage	DC24V
Dimensions	(D) Ø56mm x (L) 115mm x (H) 392mm
Finish	Black
CCT	3000K/4000K
Beam Angle	15*60°
Material	Aluminium
Driver	Remote
IP Rating	IP66
IK Rating	IK05
Luminous Flux	1669m
CRI	>90+
Colour Deviation	<3 SDCM
Lifetime	50,000 hours
Accessories	Garden Spike, Tree Mount Strap, Wall Mount Surface Extension Post, Spiked Extension Post

Control Gear	Non-dimmable, 1-10V Dimming, DALI
Warranty	5 years

## Product Accessories

<p>Garden Spike</p> 	<p>Tree Mount Strap</p> 	<p>Wall Mount</p> 	<p>Surface Extension Post</p>  <p>300/500/800/1000mm</p>
<p>Spiked Extension Post</p>  <p>300/500/800/1000mm</p>			

## Product Code

Example - VERV.SAP60.6.BLK.30.15-60.GSPK.NDM

Product	Wattage	Finish	CCT	Beam Angle	Accessories	Control Gear
VERV.SP60	6(W)	BLK (Black)	30 (00K) 40 (00K)	15-60 (°)	GSPK (Garden Spike) TRMS (Tree Mount Strap) WLMT (Wall Mount) SFEP300 (300mm Surface Extension Post) SFEP500 (500mm Surface Extension Post) SFEP800 (800mm Surface Extension Post) SFEP1000 (1000mm Surface Extension Post) SKEP300 (300mm Spiked Extension Post) SKEP500 (500mm Spiked Extension Post) SKEP800 (800mm Spiked Extension Post) SKEP1000 (1000mm Spiked Extension Post)	NDM (Non-dimmable) 1-10V (1-10V Dimming) DALI (DALI)